

AIR CURTAIN

APPLICATIONS

An air door or air curtain is a device used to prevent air or contaminants from moving from one open space to another. The most common use is a downward-facing blower fan mounted over an entrance to a building, or an opening between two spaces conditioned at different temperatures.



Working Area	3 Feet	4 Feet	5 Feet	6 Feet
--------------	--------	--------	--------	--------

FEATURES & CONSTRUCTION

- ⦿ MocCrca Powder Coated
- ⦿ M/b Assly½ HP Electric Motor
- ⦿ 1440 RPM, 6" Dia Impeller
- ⦿ FRP Blower With 'al'impeller.
- ⦿ Double Shaft type Motor.
- ⦿ Vibration Level 1 To 2 Microns
- ⦿ Noise Level + 65 DB Away From One Meter
- ⦿ Velocity12 M/S Thro Nozzle Jet
- ⦿ Supplied With Cord and Plug.
- ⦿ Operating Voltage: 220 Volts Ac (50 Hz).
- ⦿ Single Phase

LABORATORY WORK TABLE



APPLICATIONS

Our furnished Work tables in various disciplines such as Pharmaceuticals, Healthcare, Industrial Research, Chemicals, Biotechnology, Engineering, Food Labs, School, Colleges and Universities, Private and Government sector.

FEATURES & CONSTRUCTION

MOC: MS Powder Coated & Jet Black Granite Top.

Laboratory work tables are support systems for working defined laboratory environment. It is an exclusive space for placing verity of instruments and equipment's required in various laboratories.

Working Area	2 Feet	3 Feet	4 Feet
--------------	--------	--------	--------